

# UNIVERSAL™

## Suspension Fluid

### A SAFE AND ECONOMICAL REPLACEMENT FOR OEM \*NEOCON-E™ SILICON SUSPENSION FLUID

#### FEATURES AND BENEFITS:

- Silicone based, non-petroleum lubricants are 100% compatible with Hitachi \*Accu-Trac® Suspension.
- Cost-effective alternative to brand name OEM.
- Neutral pH.
- Provides necessary viscosity and stability over wide range of temperatures and more energy absorption than regular suspension/hydraulic oils.
- Economical.
- Non-corrosive properties protect equipment.

#### INTENDED USE:

Intended for use in the struts of Hitachi/Euclid \*Accu-Trac® Struts as a direct replacement for OEM \*Neocon-E™ Fluid. The Fluid is used in conjunction with helium or other inert gases in its strut application.



\*Neocon-E and Accu-Trac are trademarks of Hitachi.



SCAN  
QR code for  
more info

#### Suspension Fluid Description

#### Order#

5 Gallon Drum	51425/5G
55 Gallon Drum	51425/55G



#### APPLICATIONS:

Use in accordance with OEM specifications.

For specific technical and safety information, including Safety Data Sheet (SDS), please visit the Certol website: [www.Certol.com](http://www.Certol.com)

#### DESCRIPTION:

Universal Suspension Fluid is a silicon suspension fluid for silicone charged struts.

#### PRODUCT SPECIFICATIONS:

- pH: 6.5 - 7.5
- Odor: Non-specific.
- Color: Green-blue viscous liquid.
- Shelf Life: 5 years.
- Disposal: Dispose according to all local, state and federal regulations.