

# ProLube™ RTU

## Instrument Lubricant Ready-to-Use



ProLube RTU is a ready-to-use spray instrument lubricant formulated to improve the functionality of jointed and hinged instruments. It is water soluble, mineral oil-free and silicone-free.

### Meets AAMI ST79 Standards for Lubricants:

- Water soluble and mineral oil-free.
- Completely permeable to steam and ethylene oxide sterilants.
- Non-toxic, silicone-free, food grade lubricant system.

### The Clear Choice™:

- Water soluble formula is compatible with hot rinse cycles and steam sterilization, avoiding sticky build-up in box locks.
- Free of coloring agents that may lead to trace contamination on clean instruments before sterilization.

### Protects Instruments:

- Formula is a true solution and does not separate into component layers. No shaking required prior to application!
- Maintains smooth function of jointed and hinged items.
- Contains anti-corrosive and rust inhibiting agents to protect valuable instruments.

### Easy to Use and Reduces Cross-Contamination:

- Ready to use spray, no diluting necessary.
- Eliminates messy "dip" pans.



**Competition**  
Shake well before use.



**ProLube**  
No shaking required.

The Clear Choice™

ProLube RTU Description	Case Qty	Order#
32 oz. Spray Bottle	15	PLR/32
System Kit - (4) 32 oz. spray bottles, (5) 16 oz. empty spray bottles, 1 funnel	1	PLRSYS

## ProLube™ RTU

### Instrument Lubricant Ready-to-Use

#### Description:

ProLube RTU is a ready-to-use spray instrument lubricant formulated to improve the functionality of jointed and hinged instruments. It is water soluble, mineral oil-free and silicone-free.

#### Product Specifications:

Active Ingredients:	Non-toxic food grade lubricant with rust inhibitors and anti-corrosive agents. True solution does not separate during storage.
Dilution Ratios:	Ready-to-use, no mixing required.
pH:	4.5 - 6.0
Odor:	Non-specific.
Color:	Clear.
Shelf Life:	3 years.
Material Compatibility:	Compatible with all surgical grade metals including stainless steel, titanium, aluminum, brass and plastic instruments.

#### Product Capabilities:

ProLube RTU will easily penetrate hinges and jointed areas to improve function and prevent corrosion. This product is non-toxic and does not require rinsing after application. It is water soluble and completely permeable to steam and ethylene oxide sterilants. Because the formula is not affected by high heat sterilization, it will not create sticky build-up or yellow film inside box locks and hinges. It is safe for use in all sterilizers and with all surgical grade instruments.

ProLube RTU eliminates the messy "milk bath" and reduces overall instrument processing time. ProLube RTU is quickly applied by spraying on instruments after cleaning/rinsing and before sterilization. The spray lubricant may be applied over the entire instrument surface or targeted to jointed and hinged areas. No rinsing is required after application. Allow excess solution to drain off or lightly wipe off excess.

ProLube RTU meets AAMI ST79 (2010-2013) section 7.5.6:

*"Water-soluble instrument lubricants specifically designed for compatibility with sterilization may be used; the manufacturer's written IFU should be followed. Instrument lubricants containing mineral oil or other oil bases should not be used, except to lubricate the internal mechanism of powered instruments as specified by the manufacturer. Oil-based instrument lubricants should not be used, because the oil will coat bacteria and the instrument surface, interfering with steam contact during sterilization."*

#### Accessory Products:

Other products available from Certol include:



**ProLube™ Concentrate**  
Instrument Lubricant Concentrate



**ProEZ foam™**  
Ready-to-Use Foaming Enzymatic Spray



**ProEZ AW Quad™**  
Quadruple Enzyme Automatic Washer Detergent



**ProWash™**  
Multi-Purpose Instrument Detergent and Cart Wash